



Technical Specifications

- Package Includes:**..... Motor, Pump Tube, Hose, Storage Bracket, Barrel Adapter & Hand Nozzle
- Motor Type:**..... Open Drip Proof (IP44)
- Pump Tube Material:**.. Polypropylene, Hastelloy C-276, Carbon Graphite
- Immersion Length:**..... 39" (1000 mm) or 47" (1200 mm)
- Discharge Hose:**PVC, 6 ft (1,8 m), 1" (25 mm) I.D.
- Hand Nozzle Material:**Polypropylene, Viton
- Maximum Flow Rate:**..... 15 GPM (57 LPM) *based on water*
- Maximum Viscosity:** 1500 cps (mPas)
- Maximum Temperature:** 130° F (55° C)
- Shipping Weight:**..... 22 lbs. (9,97 kg)

RECOGNIZED COMPONENT



Intertek



DRUMS

Package P/N	Motor	Volts	Pump Tube
9400	SP-280P-V	110V	SP-PP-39
9401	SP-280P-2-V	220V	SP-PP-39

TANKS

Package P/N	Motor	Volts	Pump Tube
9402	SP-280P-V	110V	SP-PP-47
9403	SP-280P-2-V	220V	SP-PP-47



Warning: This pump is not suitable for use with Flammable/Combustible liquids.

*Note: When pumping viscosities over 1,000 cps, pump must be used intermittently to avoid potential premature failure and/or damage.