

PD 200-0

200 SERIES • SANITARY ROTARY PD PUMP

CERTIFICATIONS
FDA

PERFORMANCE AT-A-GLANCE

3 gal/min 11 L/min MAX CAPACITY	1400 rpm MAX SPEED	0.3 gal/100 rev DISPLACEMENT	165 psi 11.6 kgf/cm ² MAX PRESSURE *	1,000,000 cps (max) MAX VISCOSITY
---	--	--	---	---

CONSTRUCTION & MATERIALS

Seal Options	Elastomer Materials	Bearing Housing Materials	Rotor Housing Materials	Rotor Materials
- Single Mechanical Seal - Single O-Ring - Double O-Lip	- Viton - EPDM - Teflon Encapsulated Viton - FFKM - USP Options Available - Aflas	- Fully Machined 316 Stainless-Steel Bearing Housing - Patented Carbon Bearing Housing	- Fully Machined 316 Stainless-Steel Rotor Housing - Hastelloy	- N-60 Stainless - Alloy 88 - Hastelloy

SPECIFICATIONS

Max Temperature *	Connection Size	Net Weight	Surface Finish
401 °F 205 °C	0.375"	17 lb / 8 kg	32 Ra standard ElectroPolish standard

OPTIONS & CONFIGURATIONS

Jacketed Rotor Housing Cover	Drain Port Housing Cover	Select Coatings Available
Compac Designs Available		

*Maximum pressure and temperature ratings are based on Class E rotors. • Weight includes stainless steel bearing housing.