

PD 200

200 SERIES • SANITARY ROTARY PD PUMP

CERTIFICATIONS
FDA

PERFORMANCE AT-A-GLANCE				
8 gal/min 30 L/min MAX CAPACITY	1400 rpm MAX SPEED	0.8 gal/100 rev DISPLACEMENT	165 psi 11.6 kgf/cm ² MAX PRESSURE *	1,000,000 cps (max) MAX VISCOSITY

CONSTRUCTION & MATERIALS			
Seal Options	Elastomer Materials	Housing Materials	Rotor Materials
• Single Mechanical Seal • Single O-Ring • Double O-Lip	• Viton • EPDM • Teflon Encapsulated Viton • FFKM • USP Options Available • Aflas	• Fully Machined 316 Stainless Steel Rotor Housing • Hastelloy Rotor Housing • Fully Machined 316 Stainless Steel Bearing Housing	• Polyflex • N-60 Stainless • Alloy 88 • Hastelloy

SPECIFICATIONS			
Max Temperature *	Connection Size	Net Weight	Surface Finish
401 °F 205 °C	0.5" or 0.75"	18 lb / 8 kg	32 Ra standard 15 Ra & 20 Ra available

OPTIONS & CONFIGURATIONS		
Jacketed Rotor Housing Cover	Drain Port Housing Cover	Select Coatings Available

* Maximum pressure and temperature ratings are based on Class E rotors. - Weight includes stainless steel bearing housing.