

PD 300

300 SERIES • SANITARY ROTARY PD PUMP

CERTIFICATIONS
3-A | FDA

PERFORMANCE AT-A-GLANCE

28 gal/min 106 L/min MAX CAPACITY	1000 rpm MAX SPEED	2.8 gal/100 rev DISPLACEMENT	200 psi 14.1 kgf/cm ² MAX PRESSURE *	1,000,000 cps (max) MAX VISCOSITY
---	--	--	---	---

CONSTRUCTION & MATERIALS

Seal Options	Elastomer Materials	Housing Materials	Rotor Materials
- Single Mechanical Seal - Single Flushed Mechanical Seal - Double Mechanical Seal - Single O-Ring - Double O-Ring - Double O-Lip	- Viton - EPDM - Teflon Encapsulated Viton - FFKM - USP Options Available - Aflas	- Fully Machined 316 Stainless Steel Rotor Housing - Hastelloy Rotor Housing - Fully Machined 316 Stainless Steel Bearing Housing - Aluminum Bearing Housing	- Polyflex - N-60 Stainless - Hastelloy

SPECIFICATIONS

Max Temperature *	Connection Size	Net Weight	Surface Finish
401 °F 205 °C	1.0" or 1.5"	39 lb / 18 kg	32 Ra standard 15 Ra & 20 Ra available

OPTIONS & CONFIGURATIONS

Jacketed Rotor Housing & Cover	Drain Port Housing Cover	PRV Cover
Select Front Loaded Seals	Food First Design	Select Coatings Available

*Maximum pressure and temperature ratings are based on Class E rotors. • Weight includes stainless steel bearing housing.