

PD 602
600 SERIES • SANITARY ROTARY PD PUMP

CERTIFICATIONS
3-A | FDA

PERFORMANCE AT-A-GLANCE

318 gal/min 1204 L/min MAX CAPACITY	600 rpm MAX SPEED	53 gal/100 rev DISPLACEMENT	500 psi 35.2 kgf/cm ² MAX PRESSURE *	1,000,000 cps (max) MAX VISCOSITY
--	--------------------------------	--	--	--

CONSTRUCTION & MATERIALS

Seal Options	Elastomer Materials	Housing Materials	Rotor Materials
- Single Mechanical Seal - Double Mechanical Seal - Single O-Ring - Double O-Ring - Double O-Lip - Triple O-Lip	- Viton - EPDM - Teflon Encapsulated Viton - FFKM - USP Options Available - Aflas	- Fully Machined 316 Stainless Steel Rotor Housing - Hastelloy Rotor Housing - Fully Machined 316 Stainless Steel Bearing Housing - Painted Carbon Bearing Housing	- Polyflex - N-60 Stainless - DuraCore - Hastelloy

SPECIFICATIONS

Max Temperature *	Connection Size	Net Weight	Surface Finish
401 °F 205 °C	4.0"	900 lb / 408 kg	32 Ra standard 15 Ra & 20 Ra available

OPTIONS & CONFIGURATIONS

Jacketed Rotor Housing & Cover	Drain Port Housing Cover	PRV Cover
Select Front Loaded Seals	Swing Arm	Food First Design
Select Coatings Available		

* Maximum pressure and temperature ratings are based on Class E rotors. · Weight includes stainless steel bearing housing.