

SANITARY PROCESS EQUIPMENT

Drum Pumps



DRUM UNLOADER

- 5:1 Double Ball Pump Design
- 4.3 Cycles Per Gallon (3.8L)
- 60 Cycles/min Max Speed

FDA CE UK Ex



LOW VISCOSITY | ELECTRIC

- Flow Rate to 35 gpm (132 lpm)
- 39" (1000mm) or 47" (1200mm) lengths
- 110v or 230v Variable Speed

FDA A3 UK CE UK



LOW VISCOSITY | AIR

- Flow Rate to 28 gpm (106 lpm)
- 39" (1000mm) or 47" (1200mm) lengths
- 1/2 and 3/4 HP Motors

FDA A3 UK CE UK



HIGH VISCOSITY | ELECTRIC

- Flow Rate to 12 gpm (45 lpm)
- Maximum Viscosity 100,000 cps (mPas)
- Available with 3/4 and 1 1/2 HP Motors

FDA A3 UK CE UK



HIGH VISCOSITY | AIR

- Flow Rate to 12 gpm (45 lpm)
- Maximum Viscosity 100,000 cps (mPas)
- Available with 2, 4 and 5 HP Motors

FDA A3 CE UK



PUMP LIFT

- Lightweight & Portable
- Designed for Drums & Tanks
- Rechargeable Battery Pack

CE

Unibloc Hygienic Technologies provides a broad portfolio of powerful solutions for companies around the world.