



**UNIBLOC** 

# A SIMPLE BUT COMPLETE SOLUTION

Professionals in the biotechnology and pharmaceutical industries face unique challenges relating to cleanability, shear sensitive transfers scalability and pilot applications that other types of manufacturing don't require.

What's more, many professionals require a product that is mobile and self-sustainable, without needing other pieces of equipment to complete a processing task. With LABTOP, Unibloc has developed a patented pumping solution to address these issues.

LABTOP® is Unibloc's patented solution for the biotechnology and pharmaceutical industries. Its "plug-and-go" design is simple and efficient, it can handle small volumes, and you can easily scale it up based on your needs. That's why the LABTOP Series has been a top-selling complete pumping solution for more than 20 years.

#### Compact, Mobile and Efficient

LABTOP features a compact and highly mobile design perfect for filtration, chromatography, pilot applications, R&D and more. LABTOP makes your pumping activities simple and efficient. Each LABTOP is composed of a Unibloc pump, a motor and controller enclosed in a stainless-steel canopy, with bidirectional flow for versatility. Unibloc offers three versions of the LABTOP: the 200 Series, the 300 Series and the 400 Series.



# HIGH QUALITY, HIGHER PRESSURES

Unibloc's LABTOP series is capable of generating higher pressures than, for example, peristaltic pumps, commonly sold by our competitors. In addition, our lobe pump technology featuring all stainless-steel construction is the highest quality in the industry and designed to last a lifetime of use.



## **300 AND 400 SERIES FEATURES AND BENEFITS**

- · All stainless-steel construction
- Plug-in-the-wall unit for 1x110VAC or 1x220VAC (300 Series) or 3x220VAC (400 Series) input
- Maintain pressures up to 90 PSIG
- · Bidirectional flow
- All materials are FDA/USP Class VI compliant
- · Each unit performance tested and documented
- Full MTR documentation available upon request
- Hastelloy-C and low-ferrite SS pumps available
- Front cover drain available for full drainability
- High-grade polish and electropolish available






# **200 SERIES FEATURES AND BENEFITS**


- · All stainless-steel construction
- Plug-in-the-wall unit for 1x110VAC or 1x220VAC
- Maintain pressures up to 90 PSIG
- · Compact design
- High-grade polish and electropolish available
- · Bidirectional flow
- All materials FDA/USP Class VI compliant
- Vertical mounting for full drainability
- · Each unit performance tested and documented
- Full MTR documentation available upon request
- Hastelloy-C and low ferrite SS pumps available

### **200 SERIES LABTOP**

Dimensions				
MODEL	<b>A</b> in (mm)	<b>B</b> in (mm)	<b>Weight</b> lbs(kg)	
200-0	16.7 (425)	2.8 (70)	78 (35)	
200	17.1 (435)	3 (76)	78 (35)	
250	17.5 (443)	3.2 (82)	79 (36)	
275	17.8 (452)	3.4 (85)	80 (37)	


Specifications				
Pump Size	Max Capacity GPM (KPM)	Port Size in (mm)	RPM MAX	
PD200-0	3 (11.4)	0.375 (10)	1200	
PD200	8 (30.4)	0.5 or 0.75 (13 or 19)	1200	
PD250	11 (41.8)	0.750 (19)	1200	
PD275	14 (53.2)	0.75 or 1.0 (19 or 25)	1200	





### **300 AND 400 SERIES LABTOP**

Dimensions							
MODEL	<b>A</b> in (mm)	<b>B</b> in (mm)	<b>C</b> in (mm)	<b>D</b> in (mm)	<b>E</b> in (mm)	<b>F</b> in (mm)	<b>Weight</b> Ibs(kg)
300	11.4 (290)	18.5 (469)	18.8 (477)	5.7 (144)	4.8 (123)	2.0 (52)	99 (45)
350	11.4 (290)	19.3 (491)	18.8 (477)	5.7 (144)	4.8 (123)	2.3 (58)	103 (47)
400	13.4 (340)	25.3 (643)	28.9 (733)	7.6 (192)	6.5 (164)	1.5 (39)	257 (117)
450	13.4 (340)	25.9 (657)	28.9 (733)	7.6 (192)	6.5 (164)	1.8 (45)	301 (137)



Specifications				
Pump Size	Max Capacity GPM (KPM)	Port Size in (mm)	RPM MAX	
PD300	12.6 (47.9)	1.000 (25)	450	
PD350	18.0 (68.4)	1.5 or 2.0 (38 or 51)	450	
PD400	40.5 (153.9)	1.500 (38)	500	
PD450	54.5	2.000	500	

 $Unibloc\ Hygienic\ Technologies\ provides\ a\ broad\ portfolio\ of\ powerful\ solutions\ for\ companies\ around\ the\ world.$ 









